

# Product Data Sheet



9900 West 109<sup>th</sup> Street – Suite 100  
Overland Park, Kansas 66210  
Phone 800-755-7258 Fax 800-359-7258

## FREEZGARD® CI PLUS

### PRODUCTION LOCATION

Ogden, Utah

### PRODUCT DESCRIPTION

Produced naturally from the Great Salt Lake, FreezGard® CI Plus is specially formulated for deicing and anti-icing. It remains active (liquid) at cold temperatures while minimizing precipitates down to zero degrees Fahrenheit. FreezGard Zero is a tan to light amber liquid with a density of approximately 185 gallons per ton. A corrosion inhibitor has been added to reduce the corrosion rate.

Typical Analysis		Typical		Range
Magnesium Chloride	MgCl <sub>2</sub>	(%)	30.3	26 – 34
Sulfate	SO <sub>4</sub>	(%)	0.9	0.1 – 1.7
CI Plus Inhibitor		(%)	2.0	1.8 - 2.2
Water	H <sub>2</sub> O	(%)	66.8	65 - 70

### METHOD OF ANALYSIS

All analyses were performed by Compass Minerals Quality Control personnel. Copies of test reports are available upon request.

### APPLICATION AND STORAGE

This liquid MgCl<sub>2</sub> product in storage should be agitated regularly to minimize precipitation of undesirable solids/crystals. Application equipment should be washed daily with water. Storage equipment should be rinsed with water to prevent buildup of solids. Aluminum storage tanks or hauling equipment should not be grounded. Over application of MgCl<sub>2</sub> may result in unusually slippery road surfaces and should be avoided.

### CORROSION INHIBITOR

The CI Plus Corrosion inhibitor is a proprietary formulation that is optimized to significantly reduce metal corrosion.

### PHYSICAL PROPERTIES

Specific Gravity            1.29 +/- 0.03  
pH (5% Solution)        7 - 9  
Weight                        10.5 - 11.2 lbs./gallon

Product Description and Codes	UPC code	Product Code
Bulk		21903